



NOTES:

1. Specifications FORCE: 35N MAX.
- 1-1. INSERT FORCE: 10N MIN. INITIAL
- 1-2. WITHDRAW FORCE: 10N MIN. INITIAL
- 8-20N AFTER
- 1-3. Current rating: 1.0A
- 1-4. Voltage Rating: 30V
- 1-5. Life Test: 10000 CYCLES MIN.
- 1-6.: Dielectric withstanding: voltage 100V AC MIN.
- 1-7. Contact resistance: 30mΩ
- MAX. INITIAL: 40mΩ MAX AFTER
- 1-8. Insulation resistance: 100MΩ MIN
- 1-9. Temperature range: -30 TO +80°

APPROVALS		DATE	HORO ELECTRONICS CO., LTD			
DRAWN	D.J.LV	2017/12/26	USB CONNECTOR PART NO. U-A-39DD-W-1 SCALE: 1:1 PROJ:			
CHECKED						
APPROVALS			TITLE: USB CONNECTOR			
TOLERANCES ARE		30~1.1 ±0.30	ANGLE	UNIT: mm	SCALE: 1:1	PROJ:
		10~30 ±0.20				
		5~10 ±0.15				
		~5 ±0.10	±2'	DRAWING NO.		SHEET 1 OF 1
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			