




Specification:
 Volatage Rating:50V AC/DC
 Current Rating :1A AC/DC
 Withstaning Voltage:500V AC/Minute
 Temperature Range:-25°~+85°
 Insulation Resistance:≥100MΩ
 Contact Resistance:≤20M Ω

X1002 T- P SN2
 ① ② ③ ④

- ① Series No.
- ② Category : T-terminal
- ③ Material:P-Phosphor bronze
- ④ Plating Style:
 V01-All Gold Flash
 SN-Bright tin plating 70u";30u" Ni
 SN2-50u" Ni Min,120u" Tin Min



X1002T-PV03-E				Stamping Before Plating 30-50u" Ni/Whole Gold 3u" Min	
X1002T-PV01-E				Stamping Before Plating 30-50u" Ni/Whole Gold/Gold Flash	
X1002T-PSN2-E	Phospho Bronze	AWG#28-32	0.80mm	Stamping Before Plating 50u" Min Ni,120u"Sn Min	X1002H1
X1002T-PSN-E				Stamping Before Plating 30-50u" Ni,70-120u"Sn	
PART No	Material	Wire Range	Insulation O.D	Finish	Suitable XK&B Terminal

广东星坤科技股份有限公司
 生教 日期
 文件工程章

REVISIONS	UNSPECIFIED TOLERANCES
ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5



DSND	SCALE: N/A	MODEL TYPE:
DWN	VIEW:	1.0mm Crimp Style Connectors
CHKD	UNIT: mm/in	PART NO.:
APPD	SIZE: A4	X1002T-PSN2
		DWG NO.:
		X-X1002T-PSN2