


- NOTE:
- 1.Rating1:DC12V 0.1A
  - 2.Operating froce:200gf MAX
  - 3.Operating Temp:-40℃ ~+85℃
  - 4.Mechanical Life:200,000
  - 5.Ingress protection:IP67



Circuit Diagram

Mounting Holes

⑧	Rotator	—	1	POM	—	—
⑦	Spring	—	1	SUS	Plating silver	—
⑥	Contact	—	1	Cu Alloy	—	—
⑤	Sealed Circle	—	1	Silicone Rubber	—	—
④	Terminal	—	3	Cu Alloy	Plating silver	—
③	Lever	—	1	POM	Black	—
②	Case	—	1	PA	Black	—
①	Cover	—	1	PA	Black	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE		 ELECTRONICS CO.,LTD		
DRAWN	LIUCAN	2021.03.30				
CHECKED						
APPROVALS						
TOLERANCES ARE				30~以上	$\pm 0.30$	ANGLE
				10~30	$\pm 0.20$	
				5~10	$\pm 0.15$	
				~ 5	$\pm 0.10$	
				$\pm 2'$	UNIT: mm	SCALE: 1:1
				DRAWING NO.		PROJ:
				PART NO. K9-1268-01		
				TITLE: MICRO SWITCHS		
				SHEET 1 OF 1		

_____	A	_____	NEW	_____	_____	_____
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.